


Z113  
panel piercing  
Montagebohrung



**Mechanical characteristics**  
cable group

interface dimensions acc. to assembly code  
center conductor  
outer conductor  
mating life  
coupling torque

**Components**  
center contact  
outer contact  
other metal parts  
insulator

**Electrical characteristics**  
impedance  
frequency  
return loss

voltage proof  
insulation resistance  
contact resistance  
center contact  
outer contact

**Environmental**  
operating temp.  
RoHS compliant

**Mechanische Eigenschaften**

Kabelgruppe G 4 (RG-179B/U) : 0.3LS/1.7S, 1520A BELDEN (RGB-Kabel), 1521A BELDEN (RGB-Kabel), 1522A BELDEN (RGB-Kabel), 179DT BELDEN Precision Video Cable, RG-179B/U, RG-187A/U  
IEC 61169-24  
A4536  
solder /löt  
crimp  
>500  
Kupplungsdruckmoment 46-69 Ncm

**Bauteile**  
Innenkontakt  
Außenleiter  
sonstige Metallteile  
Isolierung

**Elektrische Eigenschaften**  
Wellenwiderstand  
Frequenz  
Rückflussdämpfung


Prüfspannung  
Isolationswiderstand  
Durchgangswiderstand  
Innenkontakt  
Außenkontakt

**Umgebung**  
Betriebstemperatur  
RoHS konform

**Materials / Material Finish / Oberfläche**  
brass / Messing gold plated / vergoldet  
brass / Messing nickel plated / vernickelt  
brass / Messing nickel plated / vernickelt  
PTFE

75 Ω  
0-3 GHz  
typ.: 1 GHz-30 dB; 2 GHz-22 dB;  
3 GHz-18 dB; 4 GHz-16 dB  
750 V<sub>eff</sub> / 50 Hz  
≥ 1 GΩ  
≤ 5 mΩ  
≤ 2,5 mΩ

-40°C / +155°C  
2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight [g]
					24.06.2015	MA	
				gepr./ appr.	01.07.2015	KL	ca./approx.
				Maßstab/ scale	Benennung/ title		
				2:1	F Bulkhead Jack F-Kabeleinbaubuchse		
				untol. Maße/ dim. without tolerances according to	Untert./ doc. type	Zeichnungsnr./ drawing no.	
					K	J01601A0008	
				Ersatz für/ replaces			
						 Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1	
a	30768	18.09.2019	KL				