

Mechanical characteristics
cable group

interface dimensions acc. to assembly code
panel piercing
centre conductor
outer conductor
mating life

Components
centre contact

tooth washer
other metal parts
crimp ferrule
insulator
o-ring

Electrical characteristics
impedance
return loss

Environmental
operating temp.
RoHS compliant

Mechanische Eigenschaften
Kabel gruppe

Steckgesicht nach Montageanleitung
Montagebohrung
Innenleiter
Außenleiter
Steckzyklen

Bauteile
Innenkontakt

Fächerscheibe
sonstige Metallteile
Crimprohr
Isolierung
O-Ring

Elektrische Eigenschaften
Wellenwiderstand
Rückflussdämpfung

Umgebung
Betriebstemperatur
RoHS konform

G 2: 0.6/3.7; 0.6L/3.7; 0.6L/3.7AF Draka; 3C-2V; 75022 V(0.6L/3.7) Sytronic Kabel GmbH; 75060 V(0.6/3.7) Sytronic Kabel GmbH; 8241 Belden; KX 6A; RG-59B/U; VK95 0.6/3.7 Percon

IEC 61169-8
A0731
Z004
Crimp
Crimp
>500

Materials / Material

CuNi1Pb1P (C97),
CuZn39Pb3
CuSn6
CuZn39Pb3, GD-ZnAl4Cu1
Cu SF w
PTFE
NBR

Finish / Oberfläche


NiP-Au

Cu2Ni5
Cu2Ni5, Zn/Cu8Ni6
Ni5

75 Ω
typ.: 1GHz-10 dB; 3 GHz-6 dB

-30°C / +85°C
2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]
			gez./ drawn	19.10.2016	MA	
			gepr./ appr.	21.11.2016	KL	ca./approx. 39
Maßstab/ scale 2:1				Benennung/ title BNC Angle Bulkhead Jack BNC-Kabelwinkeleinbaubuchse		
untol. Maße/ dim. without tolerances according to				Untert./ doc. type K		Zeichnungsnr./ drawing no. J01003A1371
Ersatz für/ replaces				Original : DIN A4 Blatt/ sheet 1 von/ of 1		



Maße/ dimensions: mm