



**Mechanical characteristics**

cables

interface dimensions acc. to assembly code

centre conductor  
outer conductor

mating life  
coupling torque

**Components**

center contact  
outer contact  
other metal parts  
crimp ferrule  
insulator

**Electrical characteristics**

impedance  
frequency  
voltage proof

**Environmental**

operating temp.  
RoHS compliant

**Mechanische Eigenschaften**

Kabel

Steckgesicht nach Montageanleitung

Innenleiter  
Außenleiter

Steckzyklen  
Kupplungs Drehmoment

**Bauteile**

Innenkontakt  
Außenkontakt  
sonstige Metallteile  
Crimprohr  
Isolierung

**Elektrische Eigenschaften**

Wellenwiderstand  
Frequenz  
Prüfspannung

**Umgebung**

Betriebstemperatur  
RoHS konform

G37 :

- (e) 2.7/7.3 AF, 2.7/7.3 CF, 213CRT7 LOW LOSS, 7810A, 9913, C2FCP, C2FP, CNT-400,
- (f) EC 400, HPF 400, LMR-400, MCR 400 AFB, SPEEDFOAM 400 HFJ, TZC 500 32, WBC-400, WCX400

(g) G55 : 9913F, MRC 400 Flex

IEC 60169-17

(a) (g) (h) A3326

Crimp  
Crimp

>500  
0,46-0,69 Nm

**Materials / Material**

CuNi1Pb1P (C97)  
CuZn39Pb3  
CuZn39Pb3  
Cu SF w  
PTFE

**Finish / Oberfläche**

Cu1Ni2Au0,8  
CuSnZn3  
CuSnZn3  
CuSnZn3

50 Ω  
0-11 GHz  
1,5 kV<sub>eff</sub> / 50 Hz

-40°C / +155°C  
2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight (g)
			gez./ drawn	10.10.2013	BJ	
			gepr./ appr.	10.10.2013	VM	ca./approx.
h	25451	08.01.2014	BJ	Maßstab/ scale: 2:1 Benennung/ title: TNC Straight Jack TNC-Kabelbuchse Untert./ doc. type: K Zeichnungsnr./ drawing no.: J01011A0055 Ersatz für/ replaces: EW980245-00 ähnl.		
g	25260	10.10.2013	BJ			
f	21949	21.06.2010	GB			
e	20137	29.07.2008	MA			
d	15875	25.08.2004	GE			
c	11328	15.03.2000	BJ	 Maße/ dimensions: mm Original : DIN A4 Blatt/ sheet 1 von/ of 1		
b	10405	12.05.1999	BA			
a	10131	26.02.1999	BA			