

Mechanical characteristics
interface dimensions acc. to

Mechanische Eigenschaften
Steckgesicht nach

61169-16 (series N)
61169-54 (series 4.3-10)

Components
centre contact
outer contact
other metal parts
insulator
gasket

Bauteile
Innenkontakt
Außenkontakt
sonstige Metallteile
Isolierung
Dichtung

Materials / Material
brass/Messing
brass/Messing
brass/Messing
PTFE
silicone/Silikon

Finish / Oberfläche
NiP-Au
CuSnZn
CuSnZn

Electrical characteristics
impedance
frequency
return loss
intermodulation

Elektrische Eigenschaften
Wellenwiderstand
Frequenz
Rückflussdämpfung
Intermodulation


50 Ω
0-6 GHz
typ.: 3 GHz-40 dB; 6 GHz-30 dB
-166 dBc 2x20 Watt


Environmental
protection class
RoHS compliant

Umgebung
Schutzklasse
RoHS konform

IP 68 (2,5 bar / 1 h) (IEC 60529)
2011/65/EU

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]	
			gez./ drawn	23.04.2018	JA		
			gepr./ appr	04.05.2018	KL	ca./approx.	49
Maßstab/ scale		Benennung/ title					
2:1 (1:1)		Adapter N - 4.3-10(HS) m-m Adapter N - 4.3-10(HS) m-m					
untol. Maße/ dim. without tolerances according to		Untert./ doc. type	Zeichnungsnr./ drawing no.				
		K	J01027C0029				
		Ersatz für/ replaces					
							
							Maße/ dimensions: mm
		Original : DIN A4					
		Blatt/ sheet 1 von/ of 1					